

Avery Dennison® MPI2105 Series

Long Term Removable StaFlat™

Revision: 9 Dated: 07/10/18

Uses:

Avery Dennison MPI2105 Easy Apply and Easy Apply RS Calendered Vinyl films is a flexible high gloss calendered vinyl. MPI2105 Series films offer exceptional value for applications requiring premium calendered film durability combined with a permanent or removable adhesive performance. MPI2105 Series offers the benefits of reduced wrinkling and air entrapment inherent in the application of decals.



Face: 3.1 mil (80 microns)
gloss calendered



Adhesive: Long Term
Removable Acrylic (gray)



Liner: 90# Easy Apply™
90# Easy Apply™ RS

Application Surfaces: Flat, simple curves (restricted to non-spill areas)

Features:

- Air egress technology helps eliminate wrinkles and bubbles
- RS provides repositionability for repositioning of graphic without great force
- Gloss finish
- Outstanding durability and outdoor performance
- Dimensionally stable liner for easy converting
- ICC profiles available on Avery Dennison's website (<https://avery-us.color-base.com>)
- Clean removability

Conversion:

- Latex Inkjet
- Solvent based inkjet
- UV inkjet*
- Mild/Eco Solvent inkjet
- Flatbed Sign-Cut
- Drum Roller Sign-Cut
- Steel Rule Die-Cutting

* For flat surfaces only, except for qualified flexible UV inks.

Common Applications:

- Vehicle
- Fleet
- Window Graphics
- Outdoor Signage
- POP/ Trade Show
- Wall Murals
- Indoor Floor Graphics

Product Data Sheet

Page 1 of 6



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI2105 Series

Long Term Removable StaFlat™

Revision: 9 Dated: 07/10/18

Physical Characteristics:

Property	Measurement	Typical Value
Caliper, face		3.1 mil (80 µm)
Caliper, adhesive		1.0mil (25 µm)
Dimensional stability		<0.04" (1.016 mm) Note: Ink loads in excess of 250% may cause increased shrinkage and/or increased initial adhesion of the printed film
Tensile at Yield		9.0 -15.0 lb/in (1.6 - 2.7 kg/cm)
Elongation		100% min.
Gloss	Hunter Gloss @ 60 degrees	85 GU
Adhesion:	15 min 24 hr	2.5 lbs/in (450 N/m) 3.5 lbs/in (613 N/m)
Flammability	FMVSS 302 ASTM E-84	Self Extinguishing Class 1 or A rating
Shelf-Life		2 years from the date of manufacture (when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.)
Durability	Vertical Exposure	Unprinted – 6 years Printed – Up to 6 years vertical. See ICS Performance Guarantee for printer specific information
Min. Application Temperature		50° F (10° C)
Service Temperature		-50° to 176°F (-45° to 80° C) (Reasonable range of temperatures which would be expected under normal environmental conditions).
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions

Product Data Sheet

Page 2 of 6



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI2105 Series

Long Term Removable StaFlat™

Revision: 9 Dated: 07/10/18

Data represents average values where applicable, and is not intended for specification purposes.

Warranty:

This Warranty applies to the Product listed in this Data Sheet. All statements, technical information (including physical and chemical characteristics) and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold subject to the Purchaser's assent and agreement that Purchaser is responsible for, and has independently determined, the suitability of such products for its purposes or its customer's purposes. Avery Dennison products are warranted to be free from defects in material and workmanship (i) for two years from the date of manufacture, or (ii) from the date of manufacture until the expiration of the period stated on the specific Product Data Sheet in effect at the time of delivery. Such time periods are subject in either case to the proper storing and application of said product, and the failure to properly store or apply the product, including without limitation the failure to follow any applicable Instructional Bulletin, negates any warranty. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited exclusively to: (a) repair or replacement of defective product without charge at Avery Dennison's plant or at the location of the product (at Avery Dennison's election), or (b) in the event repair or replacement are not commercially practical, a credit amount up to the price of the product taking into account the defect in the product in Avery Dennison's sole discretion.

THE WARRANTY EXPRESSLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. SELLER SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

AVERY DENNISON'S LIABILITY FOR DEFECTIVE PRODUCTS SHALL NOT EXCEED THE PURCHASE PRICE PAID THEREFORE BY PURCHASER AND IN NO EVENT SHALL AVERY DENNISON BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES WHETHER FORESEEABLE OR NOT, CAUSED BY DEFECTS IN SUCH PRODUCT, WHETHER SUCH DAMAGE OCCURS OR IS DISCOVERED BEFORE OR AFTER REPLACEMENT OR CREDIT, AND WHETHER OR NOT SUCH DAMAGE IS CAUSED BY AVERY DENNISON'S NEGLIGENCE.

All sales and contracts for sale of Products are subject to Purchaser's assent and agreement to this Warranty. Avery Dennison hereby objects to any terms or conditions contained in any purchase order or other communication of any kind from the Purchaser that is conflicting, inconsistent or additional to this Agreement.

▲WARNING

Failure to install the film in full compliance with Avery Dennison's installation instructions may result in personal injury or property damage. Read and follow all instructions when installing the film.

Product Data Sheet

Page 3 of 6



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI2105 Series

Long Term Removable StaFlat™

Revision: 9 Dated: 07/10/18

Related Documents:

The following Avery Dennison literature will provide complete information to the user for proper application, storage, and other requirements and is available upon request from your Avery Dennison representative or from the Avery Dennison website (www.graphics.averydennison.com).

Document Title	Reference Number
<i>Substrate Cleaning and Preparation</i>	<i>Instructional Bulletin #1.10</i>
<i>Storage, Maintenance, and Cleaning of PVC Films</i>	<i>Instructional Bulletin #1.20</i>
<i>Warranty of Avery Dennison Films</i>	<i>Instructional Bulletin #1.30</i>
<i>Multi Purpose Inkjet OEM Qualification Matrix, Durability Reference, & Troubleshooting Guide</i>	<i>Instructional Bulletin #5.80</i>
<i>Premask Recommendations</i>	<i>Instructional Bulletin #5.50</i>
<i>Removal Instructions</i>	<i>Instructional Bulletin #4.10</i>
<i>Wall Graphics</i>	<i>Instructional Bulletin #6.50</i>
<i>Application and maintenance of the Avery floor marking System</i>	<i>Instructional Bulletin #6.30</i>

Application:

Avery Dennison MPI2105 Series is designed for application onto solid surfaces with flat and simple curves such as passenger vehicles, buses, and trains. To ensure color consistency when wrapping a vehicle, ensure the material used is from one production lot # of material. Some slight color shift may occur between rolls or lots, therefore, minimizing the mixing of rolls/lots on a specific vehicle is encouraged. If multiple rolls are needed be sure to use only rolls from the same production lot.

MPI2105 Series films can be used for short-term fleet and vehicle applications. Calendered films do exhibit memory for its original shape. Subsequently, when heating and stretching the film shrinkage can be induced. As a calendered film shrinks some tenting and lifting can be expected in areas such as complex, compound and concave curves (i.e. channels). Convex curves (i.e. rivets) should be avoided when using a calendered film.

Important Note: Never use a wet application method to apply this film.

All vehicle substrates must be cleaned according to Avery Dennison recommended cleaning practices as outlined in IB #1.10 "Substrate Cleaning and Preparation".

NOTE: Signcutting of letters and graphics is not recommended with MPI2105. Cutting for the purposes of preparing sizes or shapes has proven to be feasible.

Important Note: Only use Avery Dennison recommended cleaning products and solutions (noted in IB 1.50). Cleaning and maintenance products should conform to the following:

- Free from abrasive components
- Ideally pH balanced, thus not highly acidic or alkaline (pH level between 5 and 9)
- Free from alcohol (non isopropyl), acids, ammonia, chlorine, glycol ethers, harmful detergents, petroleum distillates and phosphates

Product Data Sheet

Page 4 of 6



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI2105 Series

Long Term Removable StaFlat™

Revision: 9 Dated: 07/10/18

Unsuitable Uses:

This Avery Dennison product is not designed or recommended for the following uses. Unsuitable applications or exposure conditions include:

- Paint that is not thoroughly cured or dried
- Low surface energy substrates (i.e. Tedlar® coatings, rubber, unpainted plastic etc)
- Substrate surfaces that are not clean and smooth (little or no variation in texture)
- Painted substrates with poor paint-to-substrate, or paint-to-paint bond
- Film applied to non-Avery Dennison Films
- *Film applied to pre-existing graphics (pre approval required)*
- Watercraft below the static water line
- Watercraft which are not edge sealed
- Non-OEM painted vehicles
- Graphic removal from paint with poor adhesion or existing graphics
- Graphics exposed to oil, harsh chemicals, or gasoline vapors or spills
- Graphics where application tape must adhere to liner
- Signcutting of letters and graphics

Removability:

The removability listed in the features section “Clean removability” means removable with less than 20% adhesive residue when using appropriate heat and chemical removal methods. See Instructional Bulletin 4.10 for removal instructions. Avery Dennison will reimburse a reasonable portion of extra removal costs, not to exceed the cost of the film used on the application.

Avery Dennison does not warrant removability from the following substrates:

- **Surfaces with poor paint-to-substrate adhesion**
- **Wallboard (painted or unpainted)**
- **Pre existing graphics that must remain intact; damage to existing graphic when film is removed**
- **Improperly cured paint**
- **Oxidized or chalked substrates**
- **Horizontally exposed outdoor applications (as defined in Instructional Bulletin 1.30).**
- **Stainless Steel**

Avery Dennison makes no warranty for:

- **Paint Staining: Avery Dennison does not warrant vehicle paint staining that may be visible after removing material which has cracked or discolored. To reduce the risk of this problem, always remove the graphic at the first sign of a change in the surface of the material.**
- **Ease or speed of removal of any graphic**
- **Removal from automotive paint that is greater than 5 years old.**
- **Removal from paint that is improperly cured**
- **Removal from aged paint or metals, surface oxidation or chalking; user must test, approve and accept liability for such applications.**
- **Removal from horizontally-exposed outdoor applications.**

Product Data Sheet

Page 5 of 6



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI2105 Series

Long Term Removable StaFlat™

Revision: 9 Dated: 07/10/18

Application to Glass:

- Because of the unique properties and varieties of glass, special considerations must be considered for windows and graphic applications. Avery Dennison accepts no liability for glass breakage.
- Glass absorbs heat when exposed to sunlight. The degree of absorption across windows can vary because of shading, heating, and cooling ventilation, and insulation from window frames. These temperature differences across the window produce stress, which can cause glass breakage. The ability of glass to resist breakage because of temperature stress is affected by window size, glass thickness, glass treatments, quality, and design.
- Window cleaning methods also vary, from the type of cleaners used, to the washing methods employed. Specific chemicals used in window cleaners may affect the adhesion of pressure-sensitive graphics. Power washing methods may impact the adhesion of graphics, if the water pressure or temperature exceeds the graphic's adhesion capability. Power washing window graphics is not recommended.

Revisions are italicized

Avery Dennison® is a registered trademark of Avery Dennison Corporation
Easy Apply™ is a trademark of Avery Dennison Corporation

Product Data Sheet

Page 6 of 6



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379