

# Avery Dennison<sup>®</sup> 700 Premium Film

## Opaque films for medium-life indoor and outdoor applications

### Revision 7

### Introduction

Avery Dennison 700 Premium Films are ideal for many medium-life indoor and outdoor applications with an excellent dimensional stability. Avery Dennison 700 Premium Films are available in a very extensive range of standard colours. The embossed backing of the Easy Apply version is providing enhanced ease-of-use during application. Entrapped air can easily be rubbed out without the need to punch the vinyl film.

### Common Applications

- Flat sided trucks
- Cars and vans
- Buses
- Architectural signage
- Directional signage
- Window graphics
- Point of purchase
- Regular flat to curved surfaces



**Face Film**  
64 micron polymeric vinyl film



**Backing**  
One side coated kraft paper, 135 g/m<sup>2</sup> or Two-sided polyethylene coated kraft paper, 140g/m<sup>2</sup> with Easy Apply Technology



**Adhesive**  
Permanent, acrylic based



**Outdoor life\*\***  
Up to 8 years

### Features

- Attractive film range with 100 colours – all REACH compliant
- High gloss appearance
- Excellent dimensional stability
- Superior cutting and weeding
- Good opacity
- Blue contrast backing paper on 700 PF White and 730 PF White Matt
- New liner imprint design with square pattern to support manual conversion
- Available with Easy Apply technology, for easy bubble free application

### Conversion

- Flatbed cutters
- Friction fed cutters
- Die cutting
- Thermal transfer
- Screen printing
- Offset printing
- Cold overlaminate
- Electrostatic printing
- Latex inkjet
- Eco solvent inkjet
- Solvent inkjet
- UV curable inkjet

## General

Calliper, face film	ISO 534	64 micron
Calliper, face film & adhesive	ISO 534	85 micron
Gloss	ISO 2813	Gloss 20° 50% Matt 85° 20%
Dimensional stability	DIN 30646	0.25 mm max
Elongation	DIN 53455	120%
Adhesion, initial	FINAT FTM-1, Stainless steel	400 N/m
Adhesion, ultimate	FINAT FTM-1, Stainless steel	500 N/m
Flammability		Self extinguishing
Shelf life	Stored at 22° C/50% RH	2 years
Expected Durability**	Vertical exposure Black and White All Colours and Transparent Metallics	8 years 7 years 5 years

## Thermal

Application temperature		Minimum: + 10°C
Temperature range		-40°C to +90°C

## Chemical

Humidity resistance	200 hours exposure	No effect
Water resistance	24 hour immersion	No effect
Detergent (1% solution)	24 hour immersion	No effect
Detergent solution 65°C	8 hour immersion	No effect
Solvent resistance	Isopropyl Alcohol / Water (20/80)	No effect

**\*Important Note:** Avery Dennison® 700PF Easy Apply Film is ideal for large full colour applications and large cut graphics. Due to the nature of the adhesive and the special backing paper, not all intricate graphic designs and small lettering may be achievable. It is recommended to test the film for cutting of detailed graphics prior to production. See Avery Instructional Bulletin 2.01 for more information. For sign cutting of detailed letters and intricate graphics we recommend Avery Dennison® 700PF Premium Film without Easy Apply Technology.

### Important

Information on physical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications.

They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of any material for their specific use.

All technical data is subject to change without prior notice.

### Warranty

Avery Dennison® materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give guarantee, warranty, or make any representation contrary to the foregoing. All Avery Dennison® materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

### \*\*Expected Durability

The expected durability of Avery Dennison films are defined as the expected performance life of the Avery Dennison graphic film(s) within Zone 1 of the Avery Dennison zone system, in outdoor vertical exposure conditions.

The actual performance life will depend on a variety of factors, including selection and preparation of substrate, angle and direction of exposure, application methods, environmental conditions and cleaning/maintenance of the films.

In case of films used in areas of high temperatures or humidity, high altitudes and industrially polluted areas the performance will be further reduced.

### Expected Durability and Warranted Period Definitions

Expected durability is the expected period of time defined in the product data sheet, the product should, but is not warranted to, perform satisfactorily when applied in vertical exposure conditions as defined in Instructional Bulletin 1.30. The warranted period as defined in the appropriate ICS Performance Guarantee Bulletin, is the maximum period of time Avery Dennison will warrant the finished products performance in accordance with ICS Performance Guarantee Terms and Conditions 1.0, provided that the film is properly stored, converted and installed in accordance with Avery Dennison guidelines.

## Testing Methods

### Dimensional stability:

Is measured on a 150 x 150 mm aluminium panel to which a specimen has been applied; 72 hours after application the panel is exposed for 48 hours to + 70°C, after which the shrinkage is measured.

### Adhesion:

(FTM-1, FINAT) is measured by peeling a specimen at a 180° angle from a stainless steel or float glass panel, 24 hours after the specimen has been applied under standardised conditions. Initial adhesion is measured 20 minutes after application of the specimen.

### Flammability:

A specimen applied to aluminium is subjected to the flame of a gas burner for 15 seconds. The film should stop burning within 15 seconds after removal from the flame.

### Temperature range:

A specimen applied to stainless steel is exposed at high and low temperatures and brought back to room temperature. 1 hour after exposure the specimen is examined for any deterioration. Note: Prolonged exposure to high and low temperatures in the presence of chemicals such as solvents, acids, dyes, etc. may eventually cause deterioration.

### Chemical Resistance:

All chemical tests are conducted with test panels to which a specimen has been applied. 72 hours after application the panels are immersed in the test fluid for the given test period. 1 hour after removing the panel from the fluid, the specimen is examined for any deterioration.

### Corrosion Resistance:

A specimen applied to aluminium is exposed to saline mist (5% salt) at 35°C. After exposure, the film is removed and the panel is examined for traces of corrosion.



Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <https://graphicsap.averydennison.com/terms>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims. © 2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.