

## PRODUCT DATA SHEET



issued: 15/04/2002

# Avery® IPM I™ 7112

### Introduction

Avery IPM I 7112 is a white monomeric calendered removable self-adhesive vinyl for use on the Idanit 162Ad inkjet printer, providing good machine runnability. Because of its cost efficiency and good removability, Avery IPM I 7112 is recommended for a wide range of short term applications on flat substrates requiring easy and clean removal.

### Description

Film : 100 micron gloss white monomeric calendered vinyl  
Adhesive : **removable**, acrylic based  
Backingpaper : kraft paper, 140 g/m<sup>2</sup>

### Conversion

**Avery IPM I 7112 is specially developed for use on the Idanit 162Ad and Idanit Novo inkjet printer and has been officially approved by Idanit using BL and Magic inks.**

### Uses

- Interior & exterior signs.
- Window decoration.
- Temporary promotional and point of sale advertising and all.
- applications to flat or regular surfaces that require removability.

### Features

- Good printability and handling on Idanit 162Ad.
- Easy conversion.
- Most economical solution for short term outdoor graphics.
- Easy and clean removal (up to 1 year).



[www.averygraphics.com](http://www.averygraphics.com)

Graphics Division  
Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude – The Netherlands  
Tel +31 71 3421500 – Fax +31 71 3421538

## PRODUCT CHARACTERISTICS

Avery® IPM I™ 7112

### Physical properties

Features	Test method <sup>1</sup>	Results
Caliper, facefilm	ISO 534	100 micron
Opacity	ISO 2471	92%
Dimensional stability	DIN 30646	0.3 mm max.
Adhesion, initial	FINAT FTM-1, stainless steel	225 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	400 N/m
Flammability		Self extinguishing
Shelf life	Stored at 22° C/50-55 % RH	2 years
Removability		up to 1 year*
*Not when applied to: Nitrocellulose paints, ABS, Polystyrene, screenprinting inks (fresh), certain types of PVC		
Durability, unprinted	Vertical exposure	2 years

### Temperature range

Features	Results
Minimum application temperature:	≥ 0° C
Temperature range:	- 40 to +100 °C

#### Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

#### Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

#### 1) Test methods

More information about our test methods can be found on our website.

#### 2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

Graphics Division  
Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude – The Netherlands  
Tel +31 71 3421500 – Fax +31 71 3421538