

PRODUCT DATA SHEET



issued: **08/04/2008**

Avery® Diamond Plate Film

Introduction

Avery® Diamond Plate Film is a light diffracting metallized vinyl film. The rigid vinyl film is UV stabilized and designed for indoor and outdoor use in signs, graphics and POP displays. Addition of this film to a sign or graphic will give it a great eye-catching appeal.

Description

Facefilm: 75 micron metallized vinyl film
Adhesive: permanent, acrylic based
Backing paper: one side coated white kraft paper, 125 g/m²

Conversion

Avery Diamond Plate Film offer excellent cutting and weeding performance on a wide range of computer signmaking equipment in all popular sizes. Avery Diamond Plate Film can be thermal transfer printed, screen printed and digital printed. However, digital printing is not warranted, since the product does not permit profiling due to its nature. Settings may vary from one printer or ink system to another.

Features

- Excellent performance on flat surfaces.
- Excellent layflatness and stability during cutting and weeding.
- Medium term durability and outdoor performance.
- Excellent dimensional stability during use and application.

Recommendations for use

Avery Diamond Plate Film can generally be used for lettering and decorations on flat to slightly curved surfaces.

- Vehicle graphics
- General decorations
- Retail signage.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® Metallized Vinyl Films

Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	75 micron
Caliper, facefilm + adhesive	ISO 534	100 micron
Dimensional stability	DIN 30646	0,25 mm. max
Adhesion, initial	FINAT FTM-1, stainless steel	490 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	540 N/m
Flammability		self-extinguishing
Accelerated ageing	SAE J 1960, 2000h exposure	No negative impact on film performance
Shelf life	Stored at 22° C/50-55 % RH	1 year
Durability ²	Vertical exposure	5 years

Temperature range

Features	Results
Application temperature	Minimum: +16° C
Temperature range	-20° to + 70° C

Chemical resistance

Features	Test method ¹	Results
Humidity resistance	200 hours exposure	No effect
Corrosion resistance	120 hours exposure to corrosion	No contribution
Water resistance	48 hours immersion	No effect

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538