

900 Supercast Easy Apply™ LTR Opaque Film with Easy Apply™ LTR


Revision 4

Introduction

Avery Dennison® 900 Supercast Easy Apply LTR (Long Term Removability) is a premium quality opaque film designed for use in fleet marking and corporate identification applications requiring enhanced ease-of-use during application. The patent-pending Avery Dennison Easy Apply™ feature offers the benefits of reduced wrinkling and air entrapment inherent in the application of decals and graphics. Avery Dennison's long-term removable adhesive system offers residue-free removal over the warranted life of a graphic applied to many typical commercial and fleet vehicle surfaces.

Common Applications


- Vehicle Graphics
- Emergency vehicles
- Flat sided trucks
- Corrugated trucks
- Marine and recreational vehicles
- Trains and light rail
- Architectural
- Directional signage
- Industrial machinery
- Buses
- Windows
- Outdoor advertising



Face Film
50 micron cast PVC



Adhesive
Permanent acrylic
With Easy Apply™ and
Long Term Removability



Backing
Two side PE coated StaFlat™
paper, 145g/m²



Outdoor Life**
Up to 12 years

Features

- Super conformable cast film for reliable application on to concave, convex, compound curves and into deep recesses without the need to make incisions
- Outstanding outdoor durability and performance
- Dimensionally stable StaFlat™ backing for easy converting Superior high gloss or matte finish film
- Easy cutting and weeding
- Excellent dimensional stability after application
- Batch reference and product identification printed on liner for traceability
- Easy Apply adhesive system with air egress channels for fast and easy removal of entrapped air bubbles
- Available in 1.52m width for seamless vehicle wrapping
- Excellent long term removability for the life of the film with little or no adhesive residue
- Custom colour matching available including a range of Pantone-approved colours.

Conversion

- Flatbed cutters
- Friction fed cutters
- Die cutting
- Thermal transfer
- Screen printing
- Offset printing
- Cold overlaminating
- Electrostatic printing
- Eco solvent inkjet
- Solvent inkjet
- UV curable inkjet
- Latex inkjet

Applications

- Refer to [Instructional Bulletin 1.01](#) for Substrate Cleaning and Preparation
- Refer to [Instructional Bulletin 2.01](#) for Converting Tips for Avery Dennison Sign Films
- Refer to [Instructional Bulletin 2.09](#) for Application Instructions for Avery 900 Supercast

General

Roll width, length	615mm, 1230mm	50m
Caliper, face film	ISO 534	50 micron
Caliper, face film & adhesive	ISO 534	75 micron
Gloss	@60°	90%
Elongation	DIN 53455	150%
Dimensional stability	DIN 30646	0.4mm max
Adhesion, initial	ASTM 1000, Stainless steel	315 N/m
Adhesion, ultimate	ASTM 1000, Stainless steel	367 N/m
Removability^^	Smooth OEM painted surfaces	Up to 5 years
Shelf life	Stored at 22° C/50% RH	2 years
Flammability		Self extinguishing
Expected Durability**	Vertical exposure Black and white All colours and transparent Metallics	Up to 12 years Up to 10 years Up to 5 years

Thermal

Application temperature	Minimum: + 10°C
Temperature range	-50°C to +110°C

Chemical

Humidity resistance	120 hours exposure	No effect
Corrosion resistance	120 hours exposure	No contribution to corrosion
Water resistance	48 hour immersion	No effect
Chemical resistance	Mild acids Mild alkalis	No effect No effect
Solvent resistance	Applied to aluminium	No effect exposed to: Oils, greases, aliphatic solvents, motor oils, heptanes, kerosene, JP-4 fuel

Important

Information on physical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of any material for their specific use.

All technical data is subject to change without prior notice.

**Expected Durability

The expected durability of Avery Dennison films are defined as the expected performance life of the Avery Dennison graphic film(s) within Zone 1 of the Avery Dennison zone system, in outdoor vertical exposure conditions. The actual performance life will depend on a variety of factors, including selection and preparation of substrate, angle and direction of exposure, application methods, environmental conditions and cleaning/maintenance of the films. In case of films used in areas of high temperatures or humidity, high altitudes and industrially polluted areas the performance will be further reduced.

Warranty

Avery Dennison® materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give guarantee, warranty, or make any representation contrary to the foregoing. All Avery Dennison® materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

^^ Removability

Not removable when applied to nitrocellulose paints, fresh screen print inks, ABS, polystyrene & certain types of PVC.

Expected Durability and Warranted Period Definitions

Expected durability is the expected period of time defined in the product data sheet, the product should, but is not warranted to, perform satisfactorily when applied in vertical exposure conditions as defined in [Instructional Bulletin 1.30](#). The warranted period as defined in the appropriate ICS Performance Guarantee Bulletin, is the maximum period of time Avery Dennison will warrant the finished products performance in accordance with ICS Performance Guarantee Terms and Conditions 1.0, provided that the film is properly stored, converted and installed in accordance with Avery Dennison guidelines.

Testing Methods

Dimensional stability:

Is measured on a 150 x 150 mm aluminium panel to which a specimen has been applied; 72 hours after application the panel is exposed for 48 hours to + 70°C, after which the shrinkage is measured.

Adhesion:

(FTM-1, FINAT) is measured by peeling a specimen at a 180° angle from a stainless steel or float glass panel, 24 hours after the specimen has been applied under standardised conditions. Initial adhesion is measured 20 minutes after application of the specimen.

Flammability:

A specimen applied to aluminium is subjected to the flame of a gas burner for 15 seconds. The film should stop burning within 15 seconds after removal from the flame.

Temperature range:

A specimen applied to stainless steel is exposed at high and low temperatures and brought back to room temperature. 1 hour after exposure the specimen is examined for any deterioration. Note: Prolonged exposure to high and low temperatures in the presence of chemicals such as solvents, acids, dyes, etc. may eventually cause deterioration.

Chemical Resistance:

All chemical tests are conducted with test panels to which a specimen has been applied. 72 hours after application the panels are immersed in the test fluid for the given test period. 1 hour after removing the panel from the fluid, the specimen is examined for any deterioration.

Corrosion Resistance:

A specimen applied to aluminium is exposed to saline mist (5% salt) at 35°C. After exposure, the film is removed and the panel is examined for traces of corrosion.



Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <https://graphicsap.averydennison.com/terms>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims. © 2024 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.