

ICS Warranty Period vertical/(horizontal), up to years²

Application	Durability (unprinted, years)	Conformability ¹	Appearance	Product	Adhesive	Liner	Roll Width (m)	Print	Applications	Slip Rating	DOL 6460	DOL 1060Z	DOL 1400Z Series	Anti-Graffiti	DOL 2000 Series	DOL 2900 Series	DOL 3000 Series	
Vehicle	10	●●●●	Gloss	MPI 1105 Easy Apply RS™ LTR	LTR EA RS	SF	1.37 1.52	HP ✓		6/(3)	5	5	5	-	-	-	-	
		●●	Reflective	V-4000-101 White Easy Apply RS™ LTR	LTR EA RS	SF	1.22	HP ✓		6/(3)	5	5	-	-	-	-	-	-
	7	●●	Reflective	V-4000-101 White	Perm	SF	1.22	HP ✓		6/(3)	5	5	-	-	-	-	-	-
		●●	Gloss	MPI 2105 Easy Apply RS™	LTR EA RS	SF	1.37 1.52	✓		-	4.5	-	4	4	-	-	-	
		●●	Gloss	MPI 2002 Grey Removable	Rem	SF	1.52	HP ✓		-	4.5	-	4	4	-	-	-	
3	●	Gloss	MPI 3111 Transit Removable	Rem	SF	1.37	✓		-	-	-	-	-	-	-	2		
Window	12	●●●●	Gloss	MPI 1440 Ultra Clear	Perm	PET	1.37 1.52	✓		6/(3)	-	-	-	-	-	-	-	
	7	●●	Gloss	MPI 2041 Transparent Removable	Rem	SF	1.37 1.52	HP ✓		-	4.5	-	4	4	-	-	-	
		●●	Gloss	MPI 2040 Transparent	Perm	SF	1.37 1.52	HP ✓		-	4.5	-	4	4	-	-	-	
	5	●●	Etched	MPI Dusted Glass Easy Apply RS™	Perm EA RS	SF	1.37	✓		-	-	-	-	-	-	-	-	
	3	●	Matte	MPI 2509 PWF 50/50 Removable	Rem	1PE	1.37 1.52	L/S		2	1	-	-	-	-	-	-	
		●	Matte	MPI 2709 PWF 40/60 Removable	Rem	1PE	1.37 1.52	L/S		2	1	-	-	-	-	-	-	
2	●	Gloss	SF100-103-S Ultra Clear Removable	Rem	PET	1.37	HP L/UV		-	-	-	-	-	-	-	-		
1	●	Matte	MPI 3709 PWF 40/60 Removable	Rem	1PE	1.37 1.52	L/S		-	-	-	-	-	-	-	-		
Wall	10	●●●●	Gloss	MPI 1106 Hi-Tack Easy Apply™	Hi Perm EA	SF	1.37 1.52	HP ✓		6/(3)	5	5	5	-	-	-	-	
	7	●●	Matte	MPI 2126 Hi-Tack Easy Apply™	Hi Perm EA	SF	1.37 1.52	✓		-	4.5	-	4	4	-	-	-	
		●●	Gloss	MPI 2006 HOP Hi-Tack	Hi Perm	SF	1.37	HP ✓		-	4.5	-	4	4	-	-	-	
	4	●	Textured	MPI 2636 Textured Hi-Tack	Hi Perm	SF	1.37 1.52	HP ✓		-	-	-	-	-	-	-	-	
		●	Matte	MPI 2611 Removable	Rem	SF	1.37	✓		-	-	-	-	-	-	-	-	
	3	●	Matte	MPI 3026 Supertack	ST Perm	K	1.37	✓		-	-	-	-	-	-	-	2	
		●	Matte	MPI 8826 Wall Textile	Hi Perm	K	1.37	✓		-	-	-	-	-	-	-	-	
●		Matte	MPI 8520 Wall Paper	Perm	K	1.05	✓		-	-	-	-	-	-	-	-		
Promotional	7	●●	Gloss	MPI 2000	Perm	SF	1.37 1.52	HP ✓		-	4.5	-	4	4	-	-	-	
		●●	Matte	MPI 2120	Perm	SF	1.37 1.52	✓		-	4	-	3.5	3.5	-	-	-	
	5	●	Gloss	MPI 2904 Easy Apply™ NEW	Perm EA	SF	1.37 1.52	HP ✓		-	-	-	-	3.5	3	-	-	
		●	Matte	MPI 2923 Easy Apply™	Perm EA	SF	1.37 1.52	✓		-	-	-	-	3.5	3	-	-	
		●	Matte	MPI 2921 Removable Easy Apply™	Rem EA	SF	1.37 1.52	✓		-	-	-	-	3.5	3	-	-	
		●	Gloss	MPI 2900	Perm	SF	1.37 1.52	HP ✓		-	-	-	-	3.5	3	-	-	
	3	●	Matte	MPI 2920	Perm	SF	1.37 1.52	✓		-	-	-	-	3.5	3	-	-	
		●	Gloss	MPI 3000PP	Perm	K	1.37 1.52	HP ✓		-	-	-	-	-	-	2	-	
		●	Gloss	MPI 3001PP Removable	Rem	K	1.37 1.52	HP ✓		-	-	-	-	-	-	2	-	
		●	Matte	MPI 3021 Removable	Rem	K	1.37	✓		-	-	-	-	-	-	2	-	
●		Gloss	MPI 3300 StaFlat™	Perm	SF	1.37 1.52	HP ✓		-	-	-	-	-	-	1.5	-		
●		Gloss	MPI 3301 Removable StaFlat™	Rem	SF	1.37 1.52	HP ✓		-	-	-	-	-	-	1.5	-		
Floor	3	●	Gloss	MPI 3002 Grey Removable StaFlat™	Rem	SF	1.37 1.52	HP ✓		-	-	-	-	-	-	1.5	-	
		●	Gloss	MPI 3002PP Grey Removable	Rem	K	1.37 1.52	HP ✓		-	-	-	-	-	-	2	-	
	●	Gloss	MPI 3041PP Transparent Removable	Rem	K	1.37 1.52	✓		-	-	-	-	-	-	2	-		
●	Textured	MPI 6021 Floor Print	Rem	K	1.37	✓			P3	-	-	-	-	-	-	-		
Illuminated Signage	6	●●	Matte	MPI 2050 Translucent Matte	Perm	SF	1.37 1.52	HP ✓		-	4	-	3.5	3.5	-	-	-	

Application	Durability (unprinted, years)	Conformability ¹	Appearance	Product	Adhesive	Liner	Roll Width (m)	Print	Applications	Basis Weight (gsm)	Thread Count (/sq in)	Scrim Denier
Banner	3	●	Satin	MPI 4412 Backlit	Perm	SF	1.37 3.20 4.20 5.00	✓		440	20 x 20	1000 x 1000
		●	Matte	MPI 4330 Heavy Duty Double Sided	Perm	SF	1.37 1.60	✓		680	12 x 12	1000 x 1000
		●	Matte	MPI 4310 Double Sided	Perm	SF	1.37	✓		510	18 x 12	500 x 250
	1	●	Matte	MPI 4230 Frontlit	Perm	SF	1.37 1.60	✓		440	9 x 9	1000 x 1000
		●	Gloss	MPI 4130 Frontlit	Perm	SF	1.37 1.60 2.50	✓		440	9 x 9	1000 x 1000
		●	Matte	MPI 4350 Scrimless Double Sided	Perm	SF	1.37	✓		510	-	-
		●	Gloss	MPI 4352 Lightweight Black Back Billboard	Perm	SF	3.20 3.50 5.00	✓		300	9 x 9	500 x 500
●	Matte	MPI 4210 Economy	Perm	SF	1.37	✓		340	18 x 12	500 x 250		

Overlaminates

Product	Appearance	Product	Liner	Roll Width (m)	Slip Rating
DOL 6460	●●●● Gloss	DOL 6460 High Gloss Conformable	PET	1.22 1.37 1.52	
DOL 1060Z	●●● Gloss	DOL 1060Z	PET	1.22 1.37 1.52	
DOL 1400Z Series	●●●● Gloss	DOL 1460Z Conformable	PET	1.22 1.37 1.52	
	●●●● Matte	DOL 1480Z Conformable	PET	1.37 1.52	
Anti-Graffiti	● Gloss	DOL 4300 Anti-Graffiti	K	1.37	
DOL 2000 Series	●● Gloss	DOL 2000	K	1.37 1.52	P1
	●● Matte	DOL 2100	K	1.37 1.52	P1
	●● Satin	DOL 2200	K	1.37 1.52	
DOL 2900 Series	● Gloss	DOL 2960 NEW	PET	1.37 1.52	P1
	● Matte	DOL 2980 NEW	PET	1.37 1.52	P2
DOL 3000 Series	● Gloss	DOL 3000	K	1.37 1.52	P1
	● Matte	DOL 3100	K	1.37 1.52	P3
	● Satin	DOL 3200 Lustre	K	1.37 1.52	
Specialty	● Textured	DOL 6000 9 Month Floor Graphic	K	1.37	P3
	● Textured	DOL 5800 6 Month Floor Graphic	K	1.37	P3
	●● Gloss	DOL 4000 Crystal Clear	PET	1.37	

Conformability

- Deep Recesses / Corrugations
- Compound Curves
- Moderate Curves / Rivets
- Flat / Simple Curves

Appearance

- Clear
- Translucent
- White
- White Opaque
- Perforated White Opaque

Liner

- SF StaFlat™ 2-side PE Coated
- 1PE 1-side PE Coated
- K Coated Kraft Paper
- PET Polyester

Adhesive

- Rem Removable
- LTR Long Term Removable
- Perm Permanent
- Hi Hi-Tack
- ST Supertack
- EA Easy Apply™
- EA RS Easy Apply™ RS (Reposition & Slide)

Print Compatibility

- L Latex Inks
- S Solvent / Eco-Solvent
- UV UV-Curable
- ✓ All the above

Certified for HP Latex Inks

Application

- Outdoor Signage
- Vehicle Windows
- Marine/Watercraft³
- Textured Walls
- Illuminated Signage
- Billboard
- Transport
- Window
- Retail
- Wall
- Floor

Sustainability

- PVC-Free

Slip Ratings Overview – AS/NZ 4586:2013 Standard

Internal / Undercover Spaces	Examples	Slip ratings (wet pendulum test)		
		P1	P2	P3
Dry areas appropriate control measures ensure an area remains dry & clean when in use	Separate shops inside shopping centres Supermarket aisles (except Fresh Fruit areas)	✓	✓	✓
Transitional areas intended to be kept dry. A general exposure to water must be maintained in a dry clean condition by a facilities manager.	Entry & access areas: hotels, offices, public buildings etc. Hotel apartments, kitchens & laundries	-	✓	✓
Wet areas may be either constantly or intermittently wet or otherwise contaminated.	Entry & access areas: hotels, offices, public buildings etc. Shop & Supermarket aisles (including Fresh Fruit areas) Fast food outlets, food courts, dining areas in Shopping centres Toilet facilities in offices, hotels & shopping centres Undercover concourse areas of sports stadium. Undercover car parks Serving areas behind bars in public hotels & clubs, cold stores & freezers. Undercover loading docks. Commercial Kitchens	-	-	✓

¹ Conformability is determined by ink type, not all UV cured inks are conformable, please refer to the appropriate ICS Warranty Durability Bulletin for conformability performance
² Based on vertical exposure in Zone 2 with ICS qualified inks and printers. Please see ICS Performance Guarantee for full terms & conditions (graphicsap.averydennison.com/en/home/services/warranty.html)
³ Where the material is applied in a 'marine environment', the stated warranty period will be reduced by 40%.