

AD EDGE SEALER

Infosafe No.: LQAIO
ISSUED Date : 28/01/2021
ISSUED by: AVERY DENNISON

1. IDENTIFICATION

GHS Product Identifier

AD EDGE SEALER

Company Name

AVERY DENNISON (ABN 9200 7706 934)

Address

1124 Centre Rd Oakleigh South
VIC 3167 AUSTRALIA

Telephone/Fax Number

Tel: 03 9271 0300

Emergency phone number

Poisons Information Centre 131 126

E-mail Address

safety@ap.averydennison.com

Recommended use of the chemical and restrictions on use

Sealant

Disclaimer

Disclaimer: Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Avery Dennison Materials Pty Ltd, makes no representations as to the completeness or accuracy thereof. Information is supplied on the conditions that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Avery Dennison Materials Pty Ltd or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Flammable Liquids: Category 3

Skin Corrosion/Irritation: Category 2

Eye Damage/Irritation: Category 2A

Acute Toxicity - Inhalation: Category 4

Carcinogenicity category 1B

Germ cell mutagenicity category 1B

Hazardous to the Aquatic Environment - Long-Term Hazard: Category 3

Toxic to Reproduction: Category 1A

STOT Single Exposure: Category 3 (respiratory tract irritation)

STOT Single Exposure: Category 3 (narcotic)

STOT Repeated Exposure: Category 2

Aspiration Hazard: Category 1

Signal Word (s)

DANGER

Hazard Statement (s)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Pictogram (s)

Exclamation mark, Health hazard, Flame

**Precautionary statement – Prevention**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use carbon dioxide, extinguishing powder, foam for extinction.

Precautionary statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

Other Information

This product contains Ototoxic substances. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Xylene	1330-20-7	25-50 %
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	<=25 %
Ethylbenzene	100-41-4	5-15 %
Toluene	108-88-3	<0.5 %
Ingredients determined not to be hazardous.		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, extinguishing powder, foam

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes including hydrogen chloride, carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

3Y

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. Water may not effectively extinguish fire. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Xylene

TWA: 80 ppm, 350 mg/m³

STEL: 150 ppm, 655 mg/m³

Ethylbenzene

TWA: 100 ppm, 434 mg/m³

STEL: 125 ppm, 543 mg/m³

Toluene

TWA: 50 ppm, 191 mg/m³

STEL: 150 ppm, 574 mg/m³

Note: Sk

Oil mist

TWA: 5 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Source: Safe Work Australia

Biological Limit Values

Name: Xylenes

Determinant: Methylhippuric acids

Specimen: Creatinine in urine.

Value: 1.5 g/g

Sampling time: End of shift.

Name: Ethylbenzene

Determinant: Sum of mandelic acid and phenylglyoxylic acid

Specimen: Creatinine in urine.

Value: 0.15 g/g

Sampling time: End of shift.

Name: Toluene

Determinant: Toluene in blood

Value: 0.02 mg/L

Sampling time: Prior to last shift of workweek

Determinant: Toluene in urine

Value: 0.03 mg/L

Sampling time: End of shift.

Determinant: o-Cresol in urine*

Value: 0.3 mg/g creatinine

Sampling time: End of shift.

* with hydrolysis

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. (Recommended filter type: organic vapours) Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as PVA or nitrile rubber. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should

conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Liquid	Appearance	Colourless liquid
Colour	Colourless	Odour	Characeristic odour
Decomposition Temperature	Not available	Boiling Point	Not available
Solubility in Water	Immiscible in water	Specific Gravity	0.9
pH	Not available	Vapour Pressure	Not available
Vapour Density (Air=1)	Not available	Evaporation Rate	Not available
Odour Threshold	Not available	Viscosity	<20 mm ² /s
Volatile Component	VOC content: 72%	Partition Coefficient: n-octanol/water	Not available
Flash Point	30°C	Flammability	Flammable liquid
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available	Explosion Properties	Does not contain explosives.
Melting/Freezing Point	Not available		

10. STABILITY AND REACTIVITY

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Heat, direct sunlight, open flames or other sources of ignition. Keep away from all sources of ignition at all times.

Incompatible materials

Strong acids, strong bases. Oxidising agents.

Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide.

Possibility of hazardous reactions

Reacts with incompatible materials.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

Toxicity data for material given below.

Acute Toxicity - Oral

Acute Toxicity Estimate: 2000 - 5000 mg/kg

Method: (calculated)

Acute Toxicity - Inhalation

Acute Toxicity Estimate: >5000 ppm

Method: (calculated)

Acute Toxicity - Dermal

Acute Toxicity Estimate: 2000 - 5000 mg/kg

Method: (calculated)

Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Inhalation

Harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. May cause respiratory irritation. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

May cause genetic defects. Classified as Known or presumed to induce heritable mutations.

Carcinogenicity

May cause cancer. Classified as a Known or presumed human carcinogen.

Ethylbenzene is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Xylene is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Toluene is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

May damage fertility or the unborn child. Classified as a Known or presumed human reproductive or developmental toxicant.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs hearing organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Other Information

This product contains Ototoxic substances. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects. Using EC50's for ingredients, the calculated EC50 for the mixture is between 10 mg/l and 100 mg/l.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport:

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

Class 1: Explosives

Division 2.1: Flammable gases (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L)

Division 2.3: Toxic gases

Division 4.2: Spontaneously combustible substances

Division 5.1: Oxidising substances

Division 5.2: Organic peroxides

Class 6: Toxic or Infectious Substances (where the flammable liquid is nitromethane)

Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3

UN No: 3295

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S. (Contains Xylene & Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Packing Group: III

EMS : F-E, S-D

Special Provisions: 223

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 3295

Proper Shipping Name: Hydrocarbons, liquid, n.o.s. (Contains Xylene & Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Class: 3

Packing Group: III

Packaging Instructions (passenger & cargo): 355

Packaging Instructions (cargo only): 366

Hazard Label: Flammable liquid

Special provisions: A3, A324

U.N. Number

3295

UN proper shipping name

HYDROCARBONS, LIQUID, N.O.S.(Contains Xylene, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Transport hazard class(es)

3

Packing Group

III

Hazchem Code

3Y

IERG Number

14

IMDG Marine pollutant

No

Transport in Bulk

Not available

Special Precautions for User

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS created: January 2021

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals.

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.

