Asia Pacific August 2024

ICS Performance Guarantee Bulletin 1.11 - Canon

Introduction

The ICS Performance Guarantee combines our films with qualified OEM components to form a system which is guaranteed to be compatible and provide superior performance. You know exactly what to expect from your finished Avery Dennison graphics because your chosen combination has already withstood rigorous lab testing and met a very stringent set of durability and physical performance specifications. Please refer to Avery Dennison ICS Performance.

Guarantee Terms and Conditions 1.0 for further details.

Printer Configuration:

Avery Dennison ICS Performance Guarantee for digital inkjet printed graphics with the following Canon printers and inks;

Equipment Manufacturer



Printer name	Ink series	ICS Number
CS 6407 / 6410	IJC 640	1.11.1
CS 9065 / 9090	IJC 910	1.11.1
CS 9265 / 9290	IJC 920	1.11.1
CS 9050 / 9060 / 9065 / 9090	IJC 930	1.11.1
CS 9160	IJC 930	1.11.1
CS 9350 / 9360	IJC 932	1.11.1
Colorado 1650	UVgel 460	1.11.2
Colorado 1630	UVgel 460	1.11.2
Colorado M Series	UVgel 460	1.11.2



ICS Number 1.11.1		Warranty Period (years)					Application Substrat					
				Zor	ne 2	Zor	ne 3					rugations
Premium	Graphic Protection - DOL	Unprinted Zone 1	Indoor	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple Curves	Rivets	Compound Curves	Deep Recesses & Corrugations
MPI 1105 Easy Apply RS	Unprotected	10	-	-	_	_	-	_	-	-	-	-
MPI 1106 Hi Tack Easy Apply	DOL 6460		8	6	3	5	2	•	•	•	•	•
	DOL 1460Z DOL 1480Z		8	5	-	3	-	•	•	•	•	•
	DOL 1060Z		8	5	-	3	-	•	•	•	-	-
	SL 4530 Anti-Graffiti (DOL 4300)		8	4	-	2.5	-	•	-	-	_	-
SP 1504 Easy Apply RS	Unprotected	10	_	-	_	_	_	-	_	_	_	-
	DOL 6460		8	6	3	5	2	•	•	•	•	•
	DOL 1460Z DOL 1480Z		8	5	_	3	-	•	•	•	•	•
	DOL 1060Z		8	5	-	3	-	•	•	•	-	-
SP 1540 Ultra Clear	Unprotected	10	_	-	_	_	_	-	_	_	_	-
	DOL 6460 SP 1540		8	6	3	5	2	•	•	•	•	•
	DOL 1460Z DOL 1480Z		8	5	-	3	_	•	•	•	•	•
	DOL 1060Z		8	5	-	3	-	•	•	•	-	_

 $^{^{\}wedge} Not \, warranted \, for \, damage \, or \, fading \, of \, inks \, from \, abrasion \, or \, chemicals. \, See \, ICS \, Performance \, Guarantee \, terms \, and \, conditions \, for \, full \, details.$

ICS Number 1.11.1			anty Po	eriod (ı	Jears))		Application Substrate					
				Zon	e 2	Zor	ne 3					rrugations	
High Performance	Graphic Protection - DOL	Unprinted Zone 1	Indoor	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple Curves	Rivets	Compound Curves	Deep Recesses & Corrugations	
MPI 2000	Unprotected	7	_	_	-	-	-	_	-	_	_	-	
MPI 2002 MPI 2006 Hi Tack	DOL 1060Z		7	4.5	-	3	-	•	•	-	-	-	
MPI 2105 Easy Apply RS MPI 2120 MPI 2126 Hi Tack EA MPI 2040	DOL 2000 DOL 2100 DOL 2200		6	4	-	2.5	-	•	•	-	-	-	
MPI 2041 MPI 2050 Translucent	SL 4530 Anti-Graffiti (DOL 4300)		7	4	-	2.5	-	•	-	-	-	-	
MPI 2611 Wall Film	Unprotected	4	5^	-	-	-	-	•	-	-	-	-	
	DOL 1460Z DOL 1480Z		7	-	-	-	-	•	-	-	-	-	
	DOL 1060Z		7	-	-	-	-	•	_	-	-	-	
	DOL 2000 DOL 2100 DOL 2200		6	-	-	-	-	•	-	-	-	-	
MPI 2636 Series Textured Hi Tack	Unprotected	4	5^	-	-	-	-	•	-	-	-	-	
Intermediate													
MPI 2900 MPI 2902	Unprotected	5	_	-	-	-	-	_	-	-	_	-	
MPI 2904 EA MPI 2906 MPI 2920	DOL 2000 DOL 2100 DOL 2200		5	3.5	-	2	-	•	•	-	-	-	
MPI 2921 EA MPI 2924 EA MPI 2926	DOL 2980 DOL 2960		4	3	-	1.5	-	•	•	-	-	-	
Promotional													
MPI 3000PP MPI 3001PP	Unprotected	3	_	_	-	-	_	-	-	-	_	_	
MPI 3002PP MPI 3021 MPI 3026 Supertack MPI 3041PP	DOL 3000 DOL 3100 DOL 3200		3	2	-	1	-	•	-	-	-	-	
MPI 3300 Series	Unprotected	3	-	-	-	_	_	_	-	_	_	-	
	DOL 3000 DOL 3100 DOL 3200		3	1.5	-	0.8	_	•	-	-	-	-	

 $^{^{\}wedge} Not \ warranted \ for \ damage \ or \ fading \ of \ inks \ from \ abrasion \ or \ chemicals. See \ ICS \ Performance \ Guarantee \ terms \ and \ conditions \ for \ full \ details.$

ICS Number 1.11.1			anty Pe	eriod (į	years)		Application Substrate					
				Zon	ie 2	Zon	e 3					rugations	
Specialty	Graphic Protection - DOL	Unprinted Zone 1	Indoor	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple Curves	Rivets	Compound Curves	Deep Recesses δ Corrugations	
MPI Dusted Glass Easy Apply RS	Unprotected	5	9#	_	_	_	_	•	_	-	-	-	
	DOL 1060Z		_	4	-	2.5	_	•	-	-	-	-	
	DOL 2000 DOL 2100 DOL 2200		_	3	-	1.5	_	•	_	_	_	-	
SF 100-103-S Ultra Clear	Unprotected	5	4^	-	_	_	_	•	_	-	-	_	
SP 8526 Wall Film Textile	Unprotected	4	4^	-	-	-	-	•	-	-	-	-	
Reflective													
V-4000 Series	Unprotected	7	-	-	-	_	-	_	-	-	-	_	
	DOL 6460		_	6	3	5	2	•	•	•	•*	_	
	DOL 1460Z DOL 1480Z		-	5	-	3	-	•	•	•	•*	-	
	DOL 1060Z		-	5	-	3	-	•	•	•	-	-	
V-8000 Visiflex White	Unprotected	7	-	-	-	_	-	_	_	_	-	_	
	DOL 6460			5	_	3	_	•	•	_	-	_	
	DOL 1460Z DOL 1480Z		-	5	-	3	-	•	•	-	-	-	
	DOL 1060Z		-	5	-	3	-	•	•	-	-	-	
Perforated Window Films**													
MPI 2509 MPI 2709 PWF	Unprotected	3	_	_	-	_	_	-	_	-	-	_	
MPI 2709 PWF	DOL 6460		_	2	-	1	-	•	•	-	-	_	
	DOL 1060Z		-	1	-	6mo	-	•	•	-	-	-	
Floor Graphic System													
MPI 3002PP MPI 3041PP	DOL 3100		3mo	-	-	_	-	•	-	-	-	-	
MPI 3302 MPI 3302 EA	DOL 6000 Floor Graphics		9mo	-	-	-	-	•	-	-	-	-	

 $^{^{\}land} \, \text{Not warranted for damage or fading of inks from a brasion or chemicals}. \\ \text{See ICS Performance Guarantee terms and conditions for full details}.$

^{*} Due to the thickness of V-4000 Premium Reflective films, not all compound curves and 3D shapes may be suitable to apply to, the installer should determine the suitability of the product before attempting the installation.

^{# 5} years unprinted on the inside of external windows. 9 years unprinted on internal windows and partitions

^{**} Perforated Films must be edge-sealed as per our Instructional Bulletin 1.5

ICS Number 1.11.2		Warranty Period (years)						Application Substrate					
				Zor	ne 2	Zor	ne 3					rugations	
Premium	Graphic Protection - DOL	Unprinted Zone 1	Indoor	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple Curves	Rivets	Compound Curves	Deep Recesses & Corrugations	
MPI 1105 Easy Apply RS	Unprotected	10	-	-	_	_	-	-	-	-	-	-	
MPI 1106 Hi Tack Easy Apply	DOL 6460		8	6	3	5	2	•	•	•	-	-	
	DOL 1460Z DOL 1480Z		8	5	-	3	-	•	•	•	-	-	
	DOL 1060Z		8	5	_	3	_	•	•	•	-	-	
	SL 4530 Anti-Graffiti (DOL 4300)		8	4	_	2.5	-	•	-	-	_	-	
SP 1504 Easy Apply RS	Unprotected	10	_	-	_	_	_	_	_	_	_	-	
	DOL 6460		8	6	3	5	2	•	•	•	-	-	
	DOL 1460Z DOL 1480Z		8	5	_	3	_	•	•	•	-	_	
	DOL 1060Z		8	5	_	3	-	•	•	•	_	_	
SP 1540 Ultra Clear	Unprotected	10	_	-	_	_	_	_	_	_	_	-	
	DOL 6460 SP 1540		8	6	3	5	2	•	•	•	_	-	
	DOL 1460Z DOL 1480Z		8	5	-	3	-	•	•	•	-	-	
	DOL 1060Z		8	5	_	3	-	•	•	•	-	_	

 $^{^{\}wedge} \text{Not warranted for damage or fading of inks from a brasion or chemicals. See ICS Performance Guarantee terms and conditions for full details.}$

ICS Number 1.11.2	Warra	anty Po	eriod (ı	years))		Application Substrate					
				Zon	e 2	Zor	ne 3					rrugations
High Performance	Graphic Protection - DOL	Unprinted Zone 1	Indoor	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple Curves	Rivets	Compound Curves	Deep Recesses & Corrugations
MPI 2000	Unprotected	7	_	_	-	_	_	-	_	_	_	_
MPI 2002 MPI 2006 Hi Tack	DOL 1060Z		7	4.5	-	3	_	•	•	-	-	-
MPI 2105 Easy Apply RS MPI 2120 MPI 2126 Hi Tack EA MPI 2040	DOL 2000 DOL 2100 DOL 2200		6	4	-	2.5	-	•	•	-	-	-
MPI 2041 MPI 2050 Translucent	SL 4530 Anti-Graffiti (DOL 4300)		7	4	-	2.5	-	•	-	-	-	-
MPI 2611 Wall Film	Unprotected	4	5^	-	_	-	_	•	-	-	-	-
	DOL 1460Z DOL 1480Z		7	-	-	_	-	•	-	-	-	-
	DOL 1060Z		7	-	-	-	-	•	_	-	-	-
	DOL 2000 DOL 2100 DOL 2200		6	-	-	-	-	•	-	-	-	-
MPI 2636 Series Textured Hi Tack	Unprotected	4	5^	-	-	-	-	•	-	-	-	-
Intermediate												
MPI 2900 MPI 2902	Unprotected	5	_	-	-	-	-	-	-	-	_	-
MPI 2904 EA MPI 2906 MPI 2920	DOL 2000 DOL 2100 DOL 2200		5	3.5	-	2	-	•	•	-	-	-
MPI 2921 EA MPI 2924 EA MPI 2926	DOL 2980 DOL 2960		4	3	-	1.5	-	•	•	-	-	-
Promotional												
MPI 3000PP MPI 3001PP	Unprotected	3	_	-	-	-	-	-	_	-	-	-
MPI 3002PP MPI 3021 MPI 3026 Supertack MPI 3041PP	DOL 3000 DOL 3100 DOL 3200		3	2	_	1	_	•	-	-	-	-
MPI 3300 Series	Unprotected	3	_	-	_	_	_	-	-	-	-	-
	DOL 3000 DOL 3100 DOL 3200		3	1.5	-	0.8	-	•	-	-	-	-

 $^{^{\}wedge} Not \ warranted \ for \ damage \ or \ fading \ of \ inks \ from \ abrasion \ or \ chemicals. See \ ICS \ Performance \ Guarantee \ terms \ and \ conditions \ for \ full \ details.$

ICS Number 1.11.2		Warra	anty Pe	eriod (į	years)		Application Substrate					
				Zon	ne 2	Zon	e 3					rrugations	
Specialty	Graphic Protection - DOL	Unprinted Zone 1	Indoor	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple Curves	Rivets	Compound Curves	Deep Recesses δ Corrugations	
MPI Dusted Glass Easy Apply RS	Unprotected	5	9#	-	-	_	-	•	-	-	-	-	
	DOL 1060Z		-	4	-	2.5	-	•	-	-	-	-	
	DOL 2000 DOL 2100 DOL 2200		-	3	-	1.5	-	•	-	-	-	-	
SF 100-103-S Ultra Clear	Unprotected	5	4^	-	_	-	_	•	-	-	-	-	
SP 8526 Wall Film Textile	Unprotected	4	4^	-	-	-	-	•	-	-	-	-	
Reflective													
V-4000 Series	Unprotected	7	_	_	_	_	_	_	_	-	-	_	
	DOL 6460			6	3	5	2	•	•	•	•*	_	
	DOL 1460Z DOL 1480Z		_	5	-	3	-	•	•	•	•*	-	
	DOL 1060Z		-	5	-	3	-	•	•	•	-	-	
V-8000 Visiflex White	Unprotected	7	-	-	-	-	-	_	_	-	-	_	
	DOL 6460			5	-	3	_	•	•	_	_	_	
	DOL 1460Z DOL 1480Z		_	5	-	3	-	•	•	-	-	-	
	DOL 1060Z		-	5	-	3	-	•	•	-	-	-	
Perforated Window Films													
MPI 2509 MPI 2709 PWF	Unprotected	3	-	-	-	_	-	_	-	-	-	-	
MPI 2709 PWF	DOL 6460		_	2	-	1	_	•	•	-	-	-	
	DOL 1060Z		-	1	-	6mo	-	•	•	-	-	-	
Floor Graphic System													
MPI 3002PP MPI 3041PP	DOL 3100		3mo	_	-	_	-	•	-	-	-	-	
MPI 3302 EA	DOL 6000 Floor Graphics		9mo	-	-	-	-	•	-	-	-	-	

 $^{^{\}wedge} Not \ warranted \ for \ damage \ or \ fading \ of \ inks \ from \ abrasion \ or \ chemicals. See \ ICS \ Performance \ Guarantee \ terms \ and \ conditions \ for \ full \ details.$

^{*} Due to the thickness of V-4000 Premium Reflective films, not all compound curves and 3D shapes may be suitable to apply to, the installer should determine the suitability of the product before attempting the installation.

^{**} Perforated Films must be edge-sealed as per our Instructional Bulletin 1.5

Avery Dennison® ICS Performance Guarantee Additional information on graphics durability

Expected Durability and Potential Durability Reductions

The expected durability of Avery Dennison films are defined as the expected performance life of the Avery Dennison graphic film(s) within the AP region in outdoor vertical exposure conditions.

The actual performance life will depend on a variety of factors, including selection and preparation of substrate, angle and direction of exposure, application methods, environmental conditions and cleaning/maintenance of the films. In case of films used in areas of high temperatures or humidity, high altitudes and industrially polluted areas the performance will be further reduced.

Expected Durability and Warranted Period Definitions


Expected durability is the expected period of time defined in the product data sheet, the product should, but is not warranted to, perform satisfactorily when applied in vertical exposure conditions as defined in Instructional Bulletin
1.30. The warranted period communicated in this ICS Performance Guarantee Bulletin, is the maximum period of time Avery Dennison will warrant the finished products performance in accordance with ICS Performance Guarantee Terms and Conditions 1.0, provided that the film is properly stored, converted and installed in accordance with Avery Dennison guidelines.

Other Potential Durability Reductions

High elevations: In mountain areas UV damage is increased over exposures at sea level. This is due to the air being thinner and therefore damage of UV radiation increases significantly. Congested urban or industrial areas: Due to increased smog, pollutants and particulates in the atmosphere, applications of this kind have reduced durability expectations. Horizontal applications trap pollutants on the surface of the material, increasing the impact of UV exposure and reducing durability.


Angle and Direction of Exposure

Vertical exposure




The face of the graphic is up to 10° from vertical.

Non-vertical exposure



The face of the graphic is between 10° to 45° from vertical. The durability as stated in this ICS performance guarantee document is reduced by 50% for non-vertical applications.

Horizontal exposure



The face of the graphic is between 45° and 90° from vertical. Horizontal applications are not warranted and do not have any expectations of durability, unless otherwise stated in this ICS performance guarantee.

Asia Pacific August 2024

Zone Chart - Asia Pacific (except Australia)

Zone 2

Bangladesh	East Timor	Korea (South)	Micronesia	Rwanda	Taiwan
Bhutan	Fiji	Laos	Myanmar (Burma)	Samoa	Thailand
Burkina Faso	Guinea	Lesotho	Nepal	Singapore	Togo
Burundi	India	Madagascar	New Zealand	South Africa (East)	Turkmenistan
Cambodia	Indonesia	Malaysia	Pakistan	Sri Lanka	Vietnam
Cameroon	Ivory Coast	Mauritania	Papua New Guinea	Suriname	
China	Japan	Mauritius	Philippines	Swaziland	

Zone 3

Angola	Equatorial Guinea	Ghana	Namibia	Somalia	Zimbabwe
Botswana	Eritrea	Kenya	Niger	Tanzania	
Central African Rep.	Ethiopia	Liberia	Nigeria	Tunisia	
Chad	Gabon	Mali	Senegal	Uganda	
Congo	Gambia	Mozambique	Sierra Leone	Zambia	

 $^{^*}$ All locations (mentioned in zones 1 and 2) when installed above altitudes of 1000 meters.

Zone Chart and Map - Australia

Zone 1


Tasmania

Zone 2

Adelaide Canberra Melbourne
Albany Coffs Harbour Perth*
Brisbane* Esperance Sydney

Zone 3

Alice Springs Cook Mount Isa Broken Hill Darwin Newman Broome Dubbo Port Augusta Cairns Geraldton Port Hedland Carnarvon Kalgoorlie Telfer Townsville Ceduna Mackay



 $^{{}^*\!}All\,areas\,100km\,North\,of\,Perth\,and\,Brisbane, indicated\,by\,line\,dissecting\,map\,illustration\,of\,Australia.$

All locations mentioned in zones 1 and 2 when installed above altitudes of 1000 meters are considered Zone 3.