

# PRODUCT DATA SHEET

## Avery Dennison® SL 4530 Anti Graffiti

Issued: 09/2024

### Introduction

Avery Dennison SL 4530 Anti Graffiti is a high gloss overlaminating film that can be put on a wide range of (digitally) printed media.



#### Face Film

23 µm high gloss transparent polyester



#### Adhesive

Permanent, acrylic-based



#### Backing

One side coated bleached kraft paper, 140 g/m<sup>2</sup>



#### Durability

5 years



#### Shelf Life

2 years

### Conversion

For processing tips and reference guides please refer to Technical Bulletins:

- » 5.3 Recommended combinations and durability of Avery Dennison MPI/SP and Avery Dennison DOL/SL Series Films
- » 5.4 Processing tips for Avery Dennison DOL&SL films

### Recommendations

When laminating overprinted images, the used inks/toners should be thoroughly dry and free of (silicone) additives that might reduce/prevent proper adhesion of Avery Dennison SL 4530 Anti Graffiti.

Avery Dennison SL 4530 Anti Graffiti is an overlaminating film that protects durable images against permanent damage from graffiti, paints and UV light. Most commercially available graffiti removal fluids will allow the removal of graffiti without damaging Avery Dennison SL 4530 Anti Graffiti.

### Features

- » PVC free
- » High clarity
- » Excellent adhesion
- » Allows easy removal of graffiti
- » +Used on images created by screenprinting or digitally printed images
- » Good resistance to UV radiation and outdoor exposure conditions
- » High abrasion resistance
- » Excellent dimensional stability
- » Good resistance to chemicals and solvents

## Physical Characteristics

	Test method <sup>1</sup>	Results
<b>Product</b>		
Caliper, facefilm (micron)	ISO 534	23
Caliper, facefilm + adhesive (micron)	ISO 534	45
Dimensional stability (mm max.)	FINAT FTM 14	0.1
Shelf life (years)	Stored at 22° C/50-55 % RH	2
Durability <sup>2</sup> (years)	Vertical exposure	5
Fire Classification Rating	EN 13501-1	B-s1, d0
<b>Adhesive</b>		
Adhesion, initial (N/m)	FINAT FTM-1, stainless steel	410
Adhesion, after 24 hours (N/m)	FINAT FTM-1, stainless steel	430
<b>Temperature range</b>		
Application temperature (Minimum: °C)		see TB 5.4
Service temperature (°C to +°C)		-30 to +100
<b>Chemical properties<sup>3</sup></b>		
Chemical resistance	Mild acids	No effect
Solvent resistance	Mild alkalis	No effect
Solvent resistance	Applied to aluminum	No effect exposed to: oils, greases, aliphatic solvents, motor oils, heptane, kerosene and JP-4 fuel.

## Important

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

1) Test methods: More information about our test methods can be found on our website.

2) Durability: The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

3) Prolonged immersion in gasoline and similar fluids is not recommended.

*Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>.*

*Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.*

© 2024 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.