Avery Dennison® MPI[™] 1105 Wrapping Series





High Performance. Supreme 3D conformability. Stunning printability.

The ultimate wrapping solution -MPI[™] 1105 Wrapping Series films bring new levels of image quality, 3D conformability and printability to vehicle wraps. Outstanding colour 'pop' and an ability to cope easily with challenges such as rivets and corrugations make the MPI[™] 1105 Wrapping Series the products of choice across many different applications. MPI[™] 1105 Easy Apply RS[™] uses patented air egress technology to ensure the same application speed and convenience as Avery Dennison[®] Supreme Wrapping Film. That means endless creative possibilities for the most demanding private vehicle and commercial fleet wraps. MPI[™] 1105 Speedmaster brings you fast and effortless application and stunning graphics on your vehicle with an excellent printability on all major digital platforms, it also offers an amazing visually smooth finish.



KEY FEATURES

- Easy Apply RS[™] adhesive technology with air egress - offering repositionability and slideability
- Superb 3D conformability easy installation, conforming to the most demanding corrugations
- High performance and long-term removability with MPI™ 1105 Easy Apply RS™
- Extremely smooth finish with MPI[™] 1105 Speedmaster
- UV, solvent, eco-solvent and latex inks compatible - stunning and consistent printability
 Maximum outdoor durability, up to 10 years
- unprinted and 8 years printed*
- Covered by ICS Performance Guarantee for end-user peace of mind
- MPI[™] 1105 in combination with one of the DOL 1400 Z Series overlaminate finishes, can also be applied in more critical areas such as gas stations or tank trucks**

RECOMMENDED USES

- Partial and full wraps on private vehicles
- Partial and full wraps on commercial fleet
- Interior & exterior signs

MPI[™] 1105 Wrapping Series products

Features	MPI™ 1105 Easy Apply RS™	MPI™ 1105 Speedmaster	MPI [™] 1105
Face (50 microns Cast PVC)	~	~	~
Adhesive (grey permanent)	~	~	~
Durability (yrs) unprinted/printed* 10/8	~	~	~
Repositionable-Low Tack	~	~	×
Invisible Easy Apply™	×	~	×
Slidable	✓	×	×
Long term removable	✓	×	~



* Zone 1, EU, vertical exposure, in combination with Digital Overlaminate DOL 1460 Max. For optimal performance of the MPI[™] 1105 Wrapping Series, use Avery Dennison Digital Overlaminates (DOL).

More information: graphics.averydennison.eu/dol

** For more information please refer to Technical Bulletin 5.16 - Application of Avery Dennison[®] MPI[™] 1105 with contact to petrol



graphics.averydennison.eu Facebook LinkedIn Instagram

DISCLAIMER — All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.avergdennison.com

©2024 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison. 2024_32235 EN