

PRODUCT DATA SHEET



Avery® Coverall

issued: 19/12/2005

Introduction

Avery Coverall is a multi-purpose screenprint film for a wide variety of relatively short-term applications. It is specifically recommended in cases where old or previously used graphics have to be covered and hidden.

Description

Facefilm: 100 micron, monomerically plasticised, opaque white gloss vinyl film

Availability

	Adhesive ➔	Permanent	Removable
<i>Backing</i> Ⓛ (one side coated kraft liner)			
Standard		x	x

Conversion

Avery Coverall features excellent conversion and printing characteristics. Avery Coverall can be screenprinted with different screen inks.

For screen ink recommendations please consult Technical Bulletin No. 2.2.

Avery Coverall has excellent outdoor exposure properties.

Features

- Excellent layflatness and dimensional stability properties to ensure high output and exact registered prints.
- Excellent high opacity to hide old graphics and colour contrasts of the substrate.

Recommendations for use

- Overposting of old graphics
- Billboards
- Public transport advertising
- Short term outdoor advertising
- Posters, panels and signs at exhibitions
- Vehicle decorations
- Labels and stickers
- Point of sale promotions

Environmental, Health and Safety Regulations

The product meets the European Toy Regulations EN 71-3.

The product complies with the US CONEG Model Toxics Legislation and the EC directive 94/62/EC, article 11 on packaging and packaging waste, with reference to the acceptable levels of heavy metals, i.e. sum of heavy metals Cadmium, Mercury, Lead and Chromium (VI) is less than 100 ppm.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® Coverall

Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	100 micron
Gloss	ISO 2813, 20°	75 %
Opacity	ISO 2471	99 %
Dimensional stability	DIN 30646	0.5 mm. max
Flammability		Self extinguishing
Shelf life	Stored at 22° C/50-55 % RH	2 years
Durability ²	Vertical exposure	2 years

Adhesives

Permanent	General-purpose emulsion acrylic adhesive with high initial adhesion on most common substrates.
Removable ³⁾	General-purpose emulsion acrylic adhesive for applications where excellent removability ⁴⁾ after the intended period of use is required.

³⁾ Removability up to 1 year

⁴⁾ Not when applied to: Nitrocellulose paints, too fresh paints, ABS, Polystyrene, (fresh) screenprinting inks, certain types of PVC, Polycarbonate, PMMA.

	<u>Permanent</u>	<u>Removable</u>	
Minimum application temperature	+10°C	0°C	
Service temperature range	-40°C to +110°C	-40°C to +110°C	
Adhesion on stainless steel, initial	600 N/m	240 N/m	FTM-1
Adhesion on stainless steel, ultimate	800 N/m	320 N/m	FTM-1

Chemical properties

Features	Test method ¹	Results
Humidity resistance	120 hours exposure	No effect
Water resistance	48 hours immersion	No effect
Corrosion resistance	120 hours exposure	No contribution to corrosion
Solvent resistance	Applied to aluminium	No effect if exposed to: oils, greases, aliphatic solvents, motor oils, heptane, kerosene and JP-4 fuel

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change without notice.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538