Permanent-Kraft

Revision: 4 Dated: 04/26/22

Uses:

Avery Dennison SF100 Holographic films are light diffracting metallized, UV-stabilized, rigid vinyl films designed for indoor promotional use in signs, decals, and POP displays and short-term outdoor signage..



Face: 2.4 mil (61 microns) rigid metalized PVC



Adhesive: Clear Permanent Acrylic



Liner: 78# Kraft

Application Surfaces: Flat

Features:

- Dimensionally stable liner for easy converting
- Excellent conversion on CAD plotters
- Easy cutting & weeding
- Excellent dimensional stability
- Excellent UV, temperature, humidity, and salt-spray resistance
- Short Term Promotional Applications

Conversion:

- Thermal Die-Cutting
- Steel Rule Die-Cut

Roll Fed Sign-Cut

Common Applications:

- Architectural Signage
- Directional Signage
- Outdoor Advertising
- Vehicle Graphics
- Emblems
- Nameplates

Product Data Sheet

Page 1 of 4



www.graphics.averydennison.com Customer Service: 800-282-8379

Permanent-Kraft

Revision: 4 Dated: 04/26/22

Physical Characteristics:

Property	Measurement	Typical Value
Caliper, face		2.4 mil (61 µm)
Caliper, adhesive		1.0 mil (25 μm)
Dimensional stability		<0.025"(0.7mm)
Tensile at Yield		NA
Elongation		NA
Gloss	Hunter Gloss @ 60 degrees	NA
Adhesion: Acrylic		4.1 lbs/in (718 N/m) 4.4 lbs/in (770 N/m)
Flammability		Self Extinguishing
Shelf-Life		1 years from the date of manufacture (when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.)
Durability	Vertical Exposure	Up to 6 months
Min. Application Temperature		50° F (10° C)
Service Temperature		-40° - 176°F (-40° - 80° C) (Reasonable range of temperatures which would be expected under normal environmental conditions).
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions

Product Data Sheet

Page 2 of 4



Permanent-Kraft

Revision: 4 Dated: 04/26/22

Data represents average values where applicable, and is not intended for specification purposes.

Warranty:

This Warranty applies to the Product listed in this Data Sheet. All statements, technical information (including physical and chemical characteristics) and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold subject to the Purchaser's assent and agreement that Purchaser is responsible for, and has independently determined, the suitability of such products for its purposes or its customer's purposes. Avery Dennison products are warranted to be free from defects in material and workmanship (i) for two years from the date of manufacture, or (ii) from the date of manufacture until the expiration of the period stated on the specific Product Data Sheet in effect at the time of delivery. Such time periods are subject in either case to the proper storing and application of said product, and the failure to properly store or apply the product, including without limitation the failure to follow any applicable Instructional Bulletin, negates any warranty. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited exclusively to: (a) repair or replacement of defective product without charge at Avery Dennison's plant or at the location of the product (at Avery Dennison's election), or (b) in the event repair or replacement are not commercially practical, a credit amount up to the price of the product taking into account the defect in the product in Avery Dennison's sole discretion.

THE WARRANTY EXPRESSLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. SELLER SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

AVERY DENNISON'S LIABILITY FOR DEFECTIVE PRODUCTS SHALL NOT EXCEED THE PURCHASE PRICE PAID THEREFORE BY PURCHASER AND IN NO EVENT SHALL AVERY DENNISON BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES WHETHER FORESEEABLE OR NOT, CAUSED BY DEFECTS IN SUCH PRODUCT, WHETHER SUCH DAMAGE OCCURS OR IS DISCOVERED BEFORE OR AFTER REPLACEMENT OR CREDIT, AND WHETHER OR NOT SUCH DAMAGE IS CAUSED BY AVERY DENNISON'S NEGLIGENCE.

All sales and contracts for sale of Products are subject to Purchaser's assent and agreement to this Warranty. Avery Dennison hereby objects to any terms or conditions contained in any purchase order or other communication of any kind from the Purchaser that is conflicting, inconsistent or additional to this Agreement.

Product Data Sheet

Page 3 of 4



www.graphics.averydennison.com Customer Service: 800-282-8379

Permanent-Kraft

Revision: 4 Dated: 04/26/22

Colors & Expected Durability

Vertical Durability for Zone 1 vertical applications is noted in the chart below. Color samples are available from samples.graphics@averydennison.com, or through your sales or customer service contact. Reference Instructional Bulletin 1.30 for zones by geographic location.

KR = Kraft liner SF = StaFlat liner

	Vertical
	Durability
SF100 Holographic Film	Zone 1 Years
SF100-839-S Perm KR Confetti	6 months

Discontinued Colors:

SF100 Holographic Film	Vertical Durability Zone 1 Years	Date
SF100-847-S Perm KR		
Kaleidoscope	6 months	12/09/21

Revisions are italicized

Avery Dennison is a registered trademark of Avery Dennison Corporation

Product Data Sheet

Page 4 of 4



www.graphics.averydennison.com Customer Service: 800-282-8379