## SkyLite 20 XTRM Pro Architectural Window Film

Avery Dennison® SkyLite 20 XTRM Pro architectural window films are specialty films, engineered specifically for harsh weather conditions. These films are constructed with a unique metal alloy to provide your skylight windows exceptional durability and corrosion resistance, a stunning neutral appearance, UV-protection and extreme energy savings.

| Optical and Solar Properties        | SkyLite 20<br>XTRM Pro |        | SkyLite 20<br>XTRM Pro Poly |        |
|-------------------------------------|------------------------|--------|-----------------------------|--------|
| Pane                                | Single                 | Double | Single                      | Double |
| Visible Light Transmitted           | 23%                    | 21%    | 23%                         | 21%    |
| Visible Light Reflected (Interior)  | 31%                    | 35%    | 31%                         | 35%    |
| Visible Light Reflected (Exterior)  | 26%                    | 27%    | 26%                         | 27%    |
| Ultraviolet Block                   | 99.9%                  | 99.9%  | 99.9%                       | 99.9%  |
| Total Solar Energy Reflected        | 26%                    | 26%    | 26%                         | 26%    |
| Total Solar Energy Transmitted      | 20%                    | 17%    | 20%                         | 17%    |
| Total Solar Energy Absorbed         | 54%                    | 57%    | 54%                         | 57%    |
| Emissivity (Room Side)              | 0.84                   | 0.84   | 0.84                        | 0.84   |
| Glare Reduction                     | 74%                    | 74%    | 74%                         | 74%    |
| Selective Infrared Reduction (SIRR) | 81%                    | 85%    | 81%                         | 85%    |
| Infrared Energy Rejection (IRER)    | 64%                    | 74%    | 64%                         | 74%    |
| Shading Coefficient (SC)            | 0.42                   | 0.31   | 0.42                        | 0.31   |
| Solar Heat Gain Coefficient (SHGC)  | 0.37                   | 0.27   | 0.37                        | 0.27   |
| U Value Winter (IP)                 | 1.04                   | 0.48   | 1.04                        | 0.48   |
| U Value Winter (SI)                 | 5.91                   | 2.75   | 5.91                        | 2.75   |
| Luminous Efficacy                   | 0.55                   | 0.68   | 0.55                        | 0.68   |
| Total Solar Energy Rejected (TSER)  | 63%                    | 73%    | 63%                         | 73%    |

A537105 07/2024



For information on warranty terms, exclusions and certain limitations that apply please see our website: graphics.averydennison.com All statements, technical information and recommendations about Avery Dennison products are based upon tests and information believed to be reliable but do not constitute a guarantee or warranty of any kind. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its intended and other purposes.