

NT Natura 15i - Neutral Interior Films

Low reflectance, high performance



NT Natura 15i low reflectance neutral grey solar control film gives highly effective heat rejection, glare reduction and privacy. NT Natura 15i was developed for residential & commercial projects targeting effective energy control but requiring a subtle appearance on glass. NT Natura 15i is ideal for installation on single pane windows.

Optical and Solar Properties**	NT Natura 15i
Item Number	R058L9W
Pane	Single
Visible Light Transmitted	16%
Visible Light Reflected (Interior)	11%
Visible Light Reflected (Exterior)	9%
Ultra Violet Block	99%
Total Solar Energy Reflected	10%
Total Solar Energy Transmitted	15%
Total Solar Energy Absorbed	75%
Emissivity (Room Side)	0.86
Glare Reduction	83%
Selective InfraRed Reduction (SIRR)	85%
InfraRed Energy Rejection (IRER)	63%
Shading Coefficient	0.44
Solar Heat Gain Coeff. (G-Value)	0.38
U-Value Winter (IP)	1.05
U-Value Winter (SI)	5.80
Luminous Efficacy	0.36
Total Solar Energy Rejected (%)	62%

** Performance results are calculated on 3 mm glass using NFRC methodology and LBNL Window 5.2 software, and are subject to variations in process conditions within industry standards and are only intended for estimating purposes.

S93009 4/19



Graphics Solutions

Avery Dennison Graphics Solutions
Norton Parkway 8080
Mentor, Ohio 44060
T: 1-800-660-5559
[windowfilm.orders@averydennison.com](mailto>windowfilm.orders@averydennison.com)