

Digital Media Applications

			COMPATIBILITY			APPLICATIONS¹										OUTDOOR DURABILITY (UP TO X YEARS)								ADHESIVE REMOVABILITY			CONFORMABILITY								
Print Media		Face Finish	Adhesive	Solvent	UV-Curable	Latex Inks	Fleet/Vehicles	Transit/Bus	OEM	Vehicle Windows	Marine/Watercraft	Backlit Signs	Smooth Interior Walls	POP/Tradeshows	Window Graphics (Flat)	Outdoor Signage	Indoor Floor Graphics³	Unprinted	DOL 1000Z Series	DOL 1300Z Series	DOL 1460Z	DOL 2000 Series	DOL 3000 Series	DOL 6040	DOL 6060**	DOL 6460	Clean	Clean with Heat	Permanent	Flat with Rivets	Compound Curves	Rivets/Corrugation	Flat / Simple Curves	Flat	
SUPERCASE 7-10 YEAR DURABILITY	MPI 1105* Easy Apply RS™	Gloss	LTR	●	●	●												7	5	4	4	-	-	2	-	6 3**		●			●	●	●	●	●
	MPI 1105* Easy Apply™	Gloss	LTR	●	●	●												7	5	4	4	-	-	2	-	6 3**		●			●	●	●	●	●
	MPI 1105*	Gloss	LTR	●	●	●												7	5	4	4	-	-	2	-	6 3**		●			●	●	●	●	●
	MPI 1106 Hi Tack Easy Appy™	Gloss	Perm	●	●	●												7	5	4	4	-	-	2	-	6 3**			●		●	●	●	●	●
	MPI 1405 PVC Free Easy Apply™ RS***	Gloss	LTR	●	●	●												12	-	-	-	-	-	-	-	6 3**		●			●	●	●	●	●
	MPI 1060 Transparent	Gloss	Perm		●													7	5	4	4	-	-	2	-	5				●	●	●	●	●	●
HIGH PERFORMANCE CALENDERED 4-6 YEARS DURABILITY	MPI 2050 Translucent	Matte	Perm	●	●	●												6	5	4	4	3	2	2	3	5			●					●	●
	MPI 2077	Luster	Rem	●	●	●												1	1	1	1	1	1	1	1	1	●							●	●
	MPI 2105 Easy Apply RS™¹	Gloss	LTR	●	●	●												6	5	4	4	3	2	2	3	5		●						●	●
	MPI 2105 Easy Apply™¹	Gloss	LTR	●	●	●												6	5	4	4	3	2	2	3	5		●						●	●
	MPI 2120²	Matte	Perm	●	●	●												6	5	4	4	3	2	2	3	5			●					●	●
	MPI 2121 Transit Vinyl²	Matte	Rem	●	●	●	1											1	1	1	1	1	1	1	1	1	●							●	●
	MPI 2126 Hi Tack Easy Apply™	Matte	Perm	●	●	●												6	5	4	4	3	2	2	3	-			●					●	●
	MPI 2610 Wall Film²	Luster	Perm	●	●	●												4	3	3	3	3	2	2	3	3			●					●	●
	MPI 2611 Wall Film²	Luster	Rem	●	●	●												4	3	3	3	3	2	2	3	3	●							●	●
	MPI 2630 Textured Wall Film²	Textured	Perm	●	●	●												3	-	-	-	-	-	-	-	-			●					●	●
	MPI 2631 Textured Wall Film²	Textured	Rem	●	●	●												3	-	-	-	-	-	-	-	-	●							●	●

¹ - Refer to product and instructional bulletins for application recommendations and limitations.

² - This product has flame resistance rating of class 1 or A per the ASTM-84 (BLDG) test.

³ - Laminate required for all floor graphics. Expected durability is up to 6 months.

 Product is recommended for these applications

*MPI 1105 Supercast Film replaces MPI 1005 and supports premium printability across all approved platforms.

**DOL 6460 durability is up to 6 years vertical and 3 years horizontal for common applications

***GREENGUARD Certification Pending